


PERFECTION TK15

Perfection TK15 is the economy solution for the purpose-optimized combination of exceptional torsional stability, high breaking force, long lifetime, and optimum spooling behavior. Rotation resistant Cost-effective. Safe.



Specifications

- Ordinary lay or lang's lay, right or left lay
- 16 x 7-IWRC (K), RCN 23-2

- ✓ Multilayer Spooling
- ✓ SUPERFILL®
- ✗ PLASTFILL®

Technical data

Nominal Ø		Weight	Minimum breaking forces at rope grade		
			1,770 N/mm ²	1,960 N/mm ²	2,160 N/mm ²
mm	inch	kg/m	kN	kN	kN
7		0.23	36	40	43
8	5/16	0.30	49	53	56
9		0.38	60	67	71
9.2		0.39	63	70	77
10		0.48	74	82	87
11	7/16	0.56	90	100	106
12		0.67	108	118	126
13		0.78	126	140	148
14	9/16	0.89	146	162	172
15		1.04	168	186	197
16	5/8	1.16	191	211	224
17		1.32	215	239	253
18		1.49	241	267	284
19	3/4	1.64	269	298	316
20		1.82	298	330	350
21		2.01	328	364	386
22	7/8	2.20	360	399	423
23		2.40	394	436	463
24		2.61	429	475	504

Other rope diameters are available on request.